


## Technical details carpet tiles

|                        |                             |                          |                          |             |                     |                                   |
|------------------------|-----------------------------|--------------------------|--------------------------|-------------|---------------------|-----------------------------------|
| Manufacturing type     | Herstellungsart             | Mode fabrication         | Productie methode        |             |                     | <b>tufted 1/10"</b>               |
| Construction           | Struktur                    | Structure                | Structuur                |             |                     | <b>loop pile</b>                  |
| Pile composition       | Polmaterial                 | Couche d'usure           | Poolsamenstelling        |             |                     | <b>100% PA 6 - Econyl®</b>        |
| Dye method             | Farbgestaltung              | Coloration               | Kleurverwerking          |             |                     | <b>100% SDN</b>                   |
| Primary backing        | Trägermaterial              | Premier dossier          | Tuftdoek                 |             |                     | <b>polyester fleece</b>           |
| Secondary backing      | Rückenausüstung             | Dossier                  | Rug                      |             |                     | <b>GREENBASE modified bitumen</b> |
| Pile weight            | Poleinsatzgewicht           | Poids de velour          | Poolgewicht              | ISO 2424    | g/m <sup>2</sup>    | <b>580</b> (+/-)                  |
| Total weight           | Gesamtgewicht               | Poids total              | Totaal gewicht           | ISO 8543    | g/m <sup>2</sup>    | <b>4.400</b> (+/-)                |
| Pile height            | Polhöhe                     | Hauteur du velours       | Poolhoogte               | ISO 1766    | mm                  | <b>3,5</b> (+/-)                  |
| Total height           | Gesamtdicke                 | Epaisseur totale         | Totale dikte             | ISO 1765    | mm                  | <b>6,5</b> (+/-)                  |
| Tuft density           | Noppenzahl                  | Nombre de touffes        | Aantal punten            | ISO 1763    | /m <sup>2</sup>     | <b>155.000</b> (+/-)              |
| Size                   | Abmessung                   | Dimension                | Afmeting                 |             | cm                  | <b>50 x 50</b>                    |
| Packing                | Verpackung                  | Emballage                | Verpakking               |             |                     | <b>20 per box 5 m<sup>2</sup></b> |
| Classification         | Klassifikation              | Classement               | Gebruiksklasse           | EN 1307     |                     | <b>33 heavy commercial</b>        |
| Comfort rating         | Komfortklasse               | Classement confort       | Comfort klasse           | EN 1307     |                     | <b>LC 2</b>                       |
| Castor chair           | Stuhlleneignung             | Chaise à roulettes       | Rolstoelgeschikt         | EN 985      |                     | <b>r = 2.4 A (intensive)</b>      |
| Dimensional stability  | Dimensionstabilität         | Stabilité dimensionnelle | Dimensionele stabiliteit | EN 986      |                     | <b>≤ 0,2%</b>                     |
| Fire resistance        | Brennverhalten              | Comportement feu         | Brandgedrag              | EN 13501-1  |                     | <b>Bfl-S1 loose laid</b>          |
| Permanent antistatic   | Permanent Antistatisch      | Antistatique permanent   | Permanent antistatisch   | ISO 6356    | kV                  | <b>≤ 2,0</b>                      |
| Transversal resistance | Durchgangswiderstand        | Résistance transversale  | Doorgangsweerstand       | ISO 10965   | Ω                   | <b>≤ 10<sup>9</sup></b>           |
| Thermal resistance     | Wärmedurchlaßwiderstand     | Résistance thermique     | Warmtedoorlaatweerstand  | ISO 8302    | m <sup>2</sup> /K/W | <b>0,057</b>                      |
| Sound absorption       | Schallabsorptionsgrad       | Absorption phonique      | Geluidsabsorptie         | ISO 354     | α <sub>w</sub>      | <b>0,15</b>                       |
| Impact sound reduction | Trittschallverbesserungsmaß | Isolation phonique       | Geluidsisolatie          | ISO 10140   | ΔL <sub>w</sub>     | <b>24 dB</b>                      |
|                        |                             |                          |                          |             | ISO 10140           | ΔL                                |
| Colour fastness light  | Lichtechtheit               | Solidité à la lumière    | Lichtechtheid            | ISO 105 B02 |                     | <b>6-7</b>                        |
| Rubbing fastness       | Reibechtheit                | Solidité au frottement   | Wrijftechtheid           | ISO 105 X12 |                     | <b>4-5 wet/dry</b>                |
| Water fastness         | Wasserechtheit              | Solidité à l'eau         | Waterechtheid            | ISO 105 E01 |                     | <b>4-5 colour/staining</b>        |

Scan the QR code and discover the collection.



**EN1307**  
for use as floorcovering  
in buildings (EN 14041)  
according to the  
manufacturer's specification

**CE**  
**20**  
**EN 14041**  
**DOP 000623T-001**

**ECONYL®**  
ENDLESS POSSIBILITIES



**TWISE**

